

Technical Data Sheet

Updated: 3/9/2020

HOT SHOT'S SECRET PREMIUM RV GASOLINE ADDITIVE **Fuel Injector Cleaner and Storage Formula**

Product Overview

Hot Shot's Secret Premium RV Gasoline Additive was formulated specifically for Recreational Vehicles to include the strongest injector cleaner on the market. The injector "keep clean" formula features a highly effective Polyetheramine (PEA) detergent to clean and control deposits found in and on fuel injectors, carburetors, intake valves and combustion chambers Premium RV Gasoline Additive is infused with Hot Shot's Secret's LX4 Lubricity Extreme which provides extra wear protection to your upper cylinders and fuel system. Premium RV Gasoline Additive is compatible in gasoline with a high ethanol content. The formula also includes a water dispersant, rust and corrosion inhibitor and fuel stabilizers to keep your fuel fresh when you're not on the road.

Applications and Uses

Hot Shot's Secret Premium RV Gasoline Additive is recommended for any vehicle that runs on gasoline including carbureted, throttle body injected, multi-port injected, sequential injected and direct injected engines where fuel system cleaning and fuel storage stability is needed.

Benefits

- Improves fuel economy up to
- Cleans and restores fuel injectors
- Cleans combustion chamber deposits
- Cleans intake valve deposits
- Dissolves gums and varnish
- Smooths idle
- Improves emissions
- Stabilizes fuel for up to one year
- Lubricates upper cylinders

- Safe for all emissions equipment
- Restores performance
- Improves acceleration
- Reduces deposit formation
- Disperses moisture
- **Reduces misfires**
- Compatible with ethanol mixed fuels
- Provides corrosion protection for entire fuel system
- Reduces wear



Packaging

Available in:

16 oz. bottle

Directions for use

Add 1 ounces per 10 gallons before filling tank. Let your RV run for at least 5 minutes before storing for best results.

Gasoline	Hot Shot's Secret Premium RV Gasoline Additive	
10 gallons	1 ounce	
25 gallons	2.5 ounces	
100 gallons	10 ounces	
400 gallons	40 ounces	

Typical Properties

Property	Test Method	Result
API gravity @ 60 °F	D-1250	23.84
Flash point, °F	D-92	>178

The Safety Data Sheet is available at

http://www.hotshotsecret.com/print-documents/.